



Transponder Capacity
Global Communication Networks
High-speed Broadband
Satellite - Wireless - Fiber

Mike Termondt
Phone: 1-805-649-1384
Mobile: 1-805.794-3970
Fax: 1-805-500-4328

[HOME](#)
[PRODUCTS](#)
[CONTACT](#)
[Peng Li order form](#)


PENG LI



9.0M RING FOCUS RO & Tx/Rx ANTENNA

Add Item

SPECIFICATIONS		C-RECEIVE	C-TRANSMIT	Ku-RECEIVE	Ku-TRANSMIT
Frequency (GHz)		3.625-4.2	5.85-6.425	10.95-12.75	14-14.5
Typical Gain (dBi)		49.9	53.1	59.2	60.04
VSWR		1.25•1	1.25•1	1.25•1	1.25•1
Beamwidth:-3dB		0.55°	0.4°	0.19°	0.16°
-15dB		1.2°	0.8°	0.38°	0.32°
Antenna Noise Temperature (K)	2/4 Port Feed			2/4 Port Feed	
	2/4			2/4	
10 Elevation	35/40			60/66	
20 Elevation	27/34			50/56	
40 Elevation	24/30			44/50	
Power Handling Capability			1Kw/port		
Feed Interface		CRP-229G	CRP-159GG/137G		WR-75
Feed Insertion Loss (dB)		0.15/0.2	0.2	0.4/0.45	0.4
Port-port isolation (dB)					
Tx-Rx		35	85		
Rx-Rx, Tx-Tx Linear		30	30	30	30
Tx-Tx, Rx-Rx Linear		21	21		
Cross Polarization Isolation (dB)		35	35	35	35
			0.5		
Axial ratio, dB (Ratio)		0.5			
Sidelobes		CCLR.580•2			
MECHANICAL SPECIFICATIONS					
Azimuth Travel		±90°			
Elevation Travel		0° to 90°			
Installation Hardware					

Polarization Travel Rate		1/s			
Surface Accuracy		0.5mm			
Finish		White paint			
ENVIRONMENTAL SPECIFICATIONS					
Operational Winds		45mi/h(72km/h)			
		To60mi/h(97km/h)			
Survival Winds		125mi/h(200km/h)			
Ambient Temperature		-45 to 60			
Relative Humidity		10% to 98%			
Seismic (Survival)		0.3G's horizontal			
		0.15G's vertical			

9m Antenna, PERFORMANCE SPECIFICATIONS

The 9 Meter C-band and Ku-band antennas offer superior performance for receive only and satellite communication Tx/Rx applications.

These antennas meet the requirements for 2 satellite spacing per FCC Docket 81-704 and INTELSAT approvals.

Options:

Two port, three port, four port Rx/Tx linear or/and circular polarized feeds

Manual or motorization azimuth, elevation and polarization drive systems with controls and readouts.