



## C-Band IBUC Block Upconverter

### IBUC Advantages

Internal AGC or ALC.

Digital temperature compensation.

Calibrated input and output detectors.

Advanced customer interfaces:

- TCP/IP with embedded web page
- FSK through TX IFL cable
- RS232/485 serial ports
- Handheld terminal

1+1 switching logic and drivers.

Built-in diagnostics.

Adjustable gain.

Choice of CPR-137G or Type N output connector.

Guaranteed rated output power across the entire operating temperature range and frequency band.

Low phase noise. Exceeds IESS308/309 requirements by a minimum of 10 dB.

Compact single enclosure eliminates external booster amplifier and cables. Up to 10W without cooling fan.

Multiple transponder operation.



The revolutionary IBUC (Intelligent Block Upconverter) incorporates advanced features to take your network to new heights.

Compared to traditional 70 MHz solutions, the IBUC offers significant benefits:

- Lower terminal cost
- Simpler design and installation
- Superior RF performance
- Simplified 1+1 configuration

Unique in the IBUC are internal AGC and ALC functions to satisfy demanding applications with stringent specifications. As always, the IBUC carries Terrasat's guarantee of rated output power across the operating range from -40 to +60° C.

New interfaces connect you to the IBUC's extensive M&C facilities for network management or local access. The IBUC presents M&C information on an embedded web page via the TCP/IP connection. Serial RS232 and RS485 interfaces are also standard. The handheld terminal interface provides convenient local access to the IBUC M&C.

Other BUCs leave you with no way to verify the unit's performance. In contrast, the IBUC comes with a complete set of diagnostic tools to assist you with terminal analysis including:

- 10 MHz input detector
- Input voltage and current monitoring
- Transmit L-band input level detector
- Transmit RF output level detector
- Alarm history

The IBUC not only supports 1+1 protection – it redefines it. Instead of relying on a separate switching logic unit with its expense, we built the switching logic and drivers into the IBUC itself. Protected units monitor each other's diagnostics and, through a simple interface unit, make the decision to switch according to criteria that you select. The IBUC cloning feature enables uncomplicated 1+1 setup. Terrasat's 1+1 solution is a complete package with available dual-IBUC mounting bracket for convenient installation.

The IBUC is manufactured in our modern Morgan Hill, CA facility according to the same exacting quality processes as our PowerPlus series and OEM microwave products. Each unit undergoes rigorous testing, burn-in at elevated temperature, BER, and final testing over temperature so that you are assured of a high quality, reliable product.

## C-Band IBUC Block Upconverter Specifications

<b>L-Band Input</b>		<b>External Reference (multiplexed on TX IFL)</b>	
Frequency range		Frequency	10 MHz
Band 1	950 to 1525 MHz	Level	-8 to +3 dBm
Bands 2 & 3	1150 to 1450 MHz		
VSWR / Impedance	1.5:1 max / 50 ohms		
Connector	Type N female	<b>Local Oscillator</b>	
Input power detector range	+55 to -20 dBm	LO frequency	
Absolute accuracy	+/- 0.5 dB (CSM) +/- 1.0 dB (Burst)	Band 1	7375 MHz
<b>Gain</b>		Band 2	7875 MHz
Small Signal Gain (L-Band to RF) with attenuator set to 0 dB		Band 3	8175 MHz
5W	68 dB min	Sense	Inverting
10W	71 dB min		
20W	74 dB min		
40W	77 dB min		
Attenuator range	10 dB variable in 0.1 dB steps	<b>IBUC DC Supply</b>	
Gain flatness		Multiplexed on TX IFL	5W, 10W
Full band	3 dB p-p max	Connector	Amphenol T3106 000 (all units)
36 MHz	1 dB p-p max	Voltage / Current	
1 MHz	0.25 dB p-p max	24 +/- 4 VDC	+48 +/- 11 VDC
Gain variation over temperature		5W	3.0A max @ 24VDC
Open loop	3 dB p-p max	10W	5.0A max @ 24VDC
With AGC	1 dB p-p max	20W	na
		40W	4.5A max @ 48VDC
			7.5A max @ 48VDC
<b>RF Output</b>		<b>Monitor and Control</b>	
Frequency range		FSK (multiplexed on TX IFL)	
Band 1	5850 to 6425 MHz	Transmitter	
Band 2	6425 to 6725 MHz	Frequency	650 kHz +/- 5%
Band 3	6725 to 7025 MHz	Deviation	+/- 60 kHz
Interface	CPR-137G or Type N female (50 ohm)	Output level	-5 to +15 dBm (50 ohms)
VSWR	1.5:1 max	Receiver	
Rated output power (P1dB across temperature range and operating band)		Nominal frequency	650 kHz
5W	+37 dBm min	Locking range	+/- 32.5 kHz
10W	+40 dBm min	Input sensitivity	-15 dBm (50 ohms)
20W	+43 dBm min	Interfaces (RS232, RS485, TCP/IP and Handheld Terminal)	
40W	+46 dBm min	Connector	MS3112E-14-19S
IMD3 (2 carriers, 30 kHz apart, each at rated power minus 9 dB)	-30 dBc max	RS232/485 (2-wire)	
Level stability with ALC	+/- 0.5 dB	Data rate	Selectable 1200 to 115,200 bps
Output power detector range	Rated power to -20 dB	Data format	8 data bits, no parity, 1 stop bit, ASCII protocol
Absolute accuracy	+/- 0.5 dB (CSM) +/- 1.0 dB (Burst)	Handheld terminal data rate	9600 bps
Spurious	Complies with EN 301 443	TCP/IP	Telnet, HTTP
SSB Phase Noise			
Offset	External Reference	<b>Environmental</b>	
10 Hz	-120 dBc/Hz	Operating temperature range	-40°C to +60°C
100 Hz	-130 dBc/Hz	Relative humidity	100% non-condensing
1 kHz	-143 dBc/Hz		
10 kHz	-152 dBc/Hz	<b>Mechanical</b>	
100 kHz	-155 dBc/Hz	Size	Weight
1 MHz	-155 dBc/Hz	5W, 10W	12.2" (L) x 7.2" (W) x 3.65" (H)
			12 lbs
			310mm x 183mm x 93mm
		20W, 40W	12.2" (L) x 7.2" (W) x 7.96" (H)
			18 lbs
			310mm x 183mm x 202mm
			8.2 kg



[www.satcom-services.com](http://www.satcom-services.com)

Mike Termond

mike@satcom-services.com

Phone: 1.805.649.1384

Fax: 1.805.649.1174

\*Specifications are subject to change without notice.

Class DMC Data Sheet 02/27/04