



Ku-Band IBUC Block Upconverter

IBUC Advantages

Internal AGC or ALC.

Digital temperature compensation.

Calibrated input and output detectors.

Advanced customer interfaces:

- TCP/IP with embedded web page
- FSK through TX IFL cable
- RS232/485 serial ports
- Handheld terminal

1+1 switching logic and drivers.

Built-in diagnostics.

Adjustable gain.

Guaranteed rated output power across the entire operating temperature range and frequency band.

Low phase noise. Exceeds IESS308/309 requirements by a minimum of 5 dB.

Compact single enclosure eliminates external booster amplifier and cables. Up to 8W without cooling fan.

Multiple transponder operation.



The revolutionary IBUC (Intelligent Block Upconverter) incorporates advanced features to take your network to new heights.

Compared to traditional 70 MHz solutions, the IBUC offers significant benefits:

- Lower terminal cost
- Simpler design and installation
- Superior RF performance
- Simplified 1+1 configuration

Unique in the IBUC are internal AGC and ALC functions to satisfy demanding applications with stringent specifications. As always, the IBUC carries Terrasat's guarantee of rated output power across the operating range from -40 to +60° C.

New interfaces connect you to the IBUC's extensive M&C facilities for network management or local access. The IBUC presents M&C information on an embedded web page via the TCP/IP connection. Serial RS232 and RS485 interfaces are also standard. The handheld terminal interface provides convenient local access to the IBUC M&C.

Other BUCs leave you with no way to verify the unit's performance. In contrast, the IBUC comes with a complete set of diagnostic tools to assist you with terminal analysis including:

- 10 MHz input detector
- Input voltage and current monitoring
- Transmit L-band input level detector
- Transmit RF output level detector
- Alarm history

The IBUC not only supports 1+1 protection – it redefines it. Instead of relying on a separate switching logic unit with its expense, we built the switching logic and drivers into the IBUC itself. Protected units monitor each other's diagnostics and, through a simple interface unit, make the decision to switch according to criteria that you select. The IBUC cloning feature enables uncomplicated 1+1 setup. Terrasat's 1+1 solution is a complete package with a available dual-IBUC mounting bracket for convenient installation.

The IBUC is manufactured in our modern Morgan Hill, CA facility according to the same exacting quality processes as our PowerPlus series and OEM microwave products. Each unit undergoes rigorous testing, burn-in at elevated temperature, BER, and final testing over temperature so that you are assured of a high quality, reliable product.

Ku-Band IBUC Block Upconverter Specifications

L-Band Input		External Reference (multiplexed on TX IFL)	
Frequency range		Frequency	10 MHz
Bands 1 & 2	950 to 1450 MHz	Level	-8 to +3 dBm
Band 3	950 to 1700 MHz		
VSWR / Impedance	1.5:1 max / 50 ohms		
Connector	Type N female	Local Oscillator	
Input power detector range	<55 to >20 dBm	LO frequency	
Absolute accuracy	+/- 0.5 dB (CSM) +/- 1.0 dB (Burst)	Bands 1 & 3	12800 MHz
		Band 2	13050 MHz
Gain		Sense	Non-inverting
Small Signal Gain (L-Band to RF) with attenuator set to 0 dB			
2W	64 dB min	IBUC DC Supply	
4W	67 dB min	Multiplexed on TX IFL	2W, 4W, 8W
8W	70 dB min	Connector	Amphenol T3106 000 (all units)
16W	73 dB min	Voltage / Current	
20W	74 dB min	+24 +/- 4 VDC	+48 +/- 11 VDC
Attenuator range	10 dB variable in 0.1 dB steps	2W	1.0A max @ 24VDC
Gain flatness		4W	1.0A max @ 48VDC
Full band	3 dB p-p max	8W	3.0A max @ 48VDC
36 MHz	1 dB p-p max	16W	6.5A max @ 48VDC
1 MHz	0.25 dB p-p max	20W	7.5A max @ 48VDC
Gain variation over temperature			
Open loop	3 dB p-p max	Monitor and Control	
With AGC	1 dB p-p max	FSK (multiplexed on TX IFL)	
RF Output		Transmitter	
Frequency range		Frequency	650 kHz +/- 5%
Band 1	13.75 to 14.25 GHz	Deviation	+/- 60 kHz
Band 2	14.00 to 14.50 GHz	Output level	-5 to -15 dBm (50 ohms)
Band 3	13.75 to 14.50 GHz		
Interface	WR75 UG cover with groove	Receiver	
VSWR	1.5:1 max	Nominal frequency	650 kHz
Rated output power (P1dB across temperature range and operating band)		Locking range	+/- 32.5 kHz
2W	+33 dBm min	Input sensitivity	-15 dBm (50 ohms)
4W	+36 dBm min		
8W	+39 dBm min	Interfaces (RS232, RS485, TCP/IP and Handheld Terminal)	
16W	+42 dBm min	Connector	MS3112E-14-19S
20W	+43 dBm min	RS232/485 (2-wire)	
IMD3 (2 carriers, 30 kHz apart, each at rated power minus 9 dB)	-30 dBc max	Data rate	Selectable 1200 to 115,200 bps
Level stability with ALC	+/- 0.5 dB	Data format	8 data bits, no parity, 1 stop bit, ASCII protocol
Output power detector range	Rated power to -20 dB	Handheld terminal data rate	9600 bps
Absolute accuracy	+/- 0.5 dB (CSM) +/- 1.0 dB (Burst)	TCP/IP	Telnet, HTTP
Sporious	Complies with EN 301 428		
SSB Phase Noise		Environmental	
Offset	External Reference	IBUC	
10 Hz	-120 dBc/Hz	Size	Weight
100 Hz	-130 dBc/Hz	2W, 4W	12 lbs
1 kHz	-143 dBc/Hz	310mm x 183mm x 93mm	5.4 kg
10 kHz	-152 dBc/Hz	8W	12 lbs
100 kHz	-155 dBc/Hz	348mm x 183mm x 93mm	5.4 kg
1 MHz	-155 dBc/Hz	16W, 20W	18 lbs
		348mm x 183mm x 202mm	8.2 kg

*Specifications are subject to change without notice.



www.satcom-services.com

Mike Termondt

mike@satcom-services.com

Phone: 1.805.649.1384

Fax: 1.805.649.1174

KuBand IBUC Data Sheet 02/27/04